

台灣蠟品股份有限公司
TAIWAN WAX COMPANY, LTD.

62146 嘉義縣民雄工業區中正路 1 號
NO. 1, Chung-Cheng Road,
Minsiung Industrial Park,
Chiayi 62146, Taiwan, R.O.C.
Tel : +886-5-2219180 ; Fax : +886-5-2219182
E-mail : service@wax.com.tw

WAX-156

CERTIFICATE OF ANALYSIS

Customer : ARK CO., LTD. Analysis date : DEC. 25. 2023
Commodity : PARAFFIN WAX 156°F Lot NO. : 156F1225-23
Quantity : 300kgs Vessel : OOCL NEW ZEALAND
PO NO. : AS12425 Report NO. : TQ-1130126

Analysis Item (分析項目)	Result (結果)	Specification (規格)	Test Method (測試方法)
Specific Gravity at 100°C (比重)	0.782	0.76~0.79	ASTM D1298
Melting Point, °F (熔點)	155.1	153~158	ASTM D 87
Needle Penetration, (針入度) mm/10 at 77°F	19.0	14.0~20.0	ASTM D1321
Kinematic Viscosity, (動黏度) cSt. at 212°F	6.908	6.0~7.5	ASTM D445
Oil Content, wt% (油含量)	0.798	Max.1.0	ASTM D721
Saybolt Color (色度)	+30	Min.+10	ASTM D156
Flash Point, °C (閃火點)	263	Min.240	ASTM D92
Conclusion (結論)	ON (*) OFF ()		

Remark (備註):

- Please keep the product away from open flames, hot surfaces, sources of ignition, and direct sunlight.
- Unit conversions: °C = (°F - 32) / 1.8 ; °F = (°C × 1.8) + 32.

Prepared by :

