

台灣蠟品股份有限公司

TAIWAN WAX COMPANY, LTD.

62146 嘉義縣民雄工業區中正路 1 號

NO. 1, Chung-Cheng Road,

Minsiung Industrial Park,

Chiayi 62146, Taiwan, R.O.C.

Tel : +886-5-2219180 ; Fax : +886-5-2219182

E-mail : service@wax.com.tw

WAX-160

CERTIFICATE OF ANALYSIS

Customer : ARK CO., LTD. Analysis date : NOV. 08. 2023
Commodity : PARAFFIN WAX 160°F Lot NO. : 160F1108-23
Quantity : 2kg Vessel : ----
PO NO. : ---- Report NO. : ----

Analysis Item (分析項目)	Result (結果)	Specification (規格)	Test Method (測試方法)
Specific Gravity at 100°C (比重)	0.781	0.77~0.80	ASTM D1298
Melting Point, °F (熔點)	159.1	158~162	ASTM D 87
Needle Penetration, (針入度) mm/10 at 77°F	16.0	14.0~20.0	ASTM D1321
Kinematic Viscosity, (動黏度) cSt. at 212°F	6.757	6.4~7.5	ASTM D445
Oil Content, wt% (油含量)	0.865	Max.1.0	ASTM D721
Saybolt Color (色度)	+30	Min.+10	ASTM D156
Flash Point, °C (閃火點)	262	Min.250	ASTM D92
Conclusion (結論)	ON (*) OFF ()		

Remark (備註):

1. Please keep the product away from open flames, hot surfaces, sources of ignition, and direct sunlight.
2. Unit conversions: °C = (°F - 32) / 1.8 ; °F = (°C × 1.8) + 32.

Prepared by :

侯福麟

台灣蠟品股份有限公司

TAIWAN WAX COMPANY, LTD.

62146 嘉義縣民雄工業區中正路 1 號

NO. 1, Chung-Cheng Road,

Minsiung Industrial Park,

Chiayi 62146, Taiwan, R.O.C.

Tel : +886-5-2219180 ; Fax : +886-5-2219182

E-mail : service@wax.com.tw

WAX-160

CERTIFICATE OF ANALYSIS

Customer	: ARK CO., LTD.	Analysis date	: JUN. 20. 2023
Commodity	: PARAFFIN WAX 160°F	Lot NO.	: 160F0620-23
Quantity	: 2kg	Vessel	: ----
PO NO.	: ----	Report NO.	: ----

Analysis Item (分析項目)	Result (結果)	Specification (規格)	Test Method (測試方法)
Specific Gravity at 100°C (比重)	0.781	0.77~0.80	ASTM D1298
Melting Point, °F (熔點)	159.3	158~162	ASTM D 87
Needle Penetration, (針入度) mm/10 at 77°F	16.0	14.0~20.0	ASTM D1321
Kinematic Viscosity, (動黏度) cSt. at 212°F	6.793	6.4~7.5	ASTM D445
Oil Content, wt% (油含量)	0.858	Max.1.0	ASTM D721
Saybolt Color (色度)	+30	Min.+10	ASTM D156
Flash Point, °C (閃火點)	262	Min.250	ASTM D92
Conclusion (結論)	ON (*) OFF ()		

Remark (備註):

1. Please keep the product away from open flames, hot surfaces, sources of ignition, and direct sunlight.
2. Unit conversions: °C = (°F - 32) / 1.8 ; °F = (°C × 1.8) + 32.

Prepared by :

侯福麟

台灣蠟品股份有限公司

TAIWAN WAX COMPANY, LTD.

62146 嘉義縣民雄工業區中正路 1 號

NO. 1, Chung-Cheng Road,

Minsiung Industrial Park,

Chiayi 62146, Taiwan, R.O.C.

Tel : +886-5-2219180 ; Fax : +886-5-2219182

E-mail : service@wax.com.tw

WAX-160

CERTIFICATE OF ANALYSIS

Customer	: ARK CO., LTD.	Analysis date	: FEB. 15. 2023
Commodity	: PARAFFIN WAX 160°F	Lot NO.	: 160F0215-23
Quantity	: 2kg	Vessel	: ----
PO NO.	: ----	Report NO.	: ----

Analysis Item (分析項目)	Result (結果)	Specification (規格)	Test Method (測試方法)
Specific Gravity at 100°C (比重)	0.781	0.77~0.80	ASTM D1298
Melting Point, °F (熔點)	159.0	158~162	ASTM D 87
Needle Penetration, (針入度) mm/10 at 77°F	16.0	14.0~20.0	ASTM D1321
Kinematic Viscosity, (動黏度) cSt. at 212°F	6.629	6.4~7.5	ASTM D445
Oil Content, wt% (油含量)	0.879	Max.1.0	ASTM D721
Saybolt Color (色度)	+30	Min.+10	ASTM D156
Flash Point, °C (閃火點)	262	Min.250	ASTM D92
Conclusion (結論)	ON (*) OFF ()		

Remark (備註):

1. Please keep the product away from open flames, hot surfaces, sources of ignition, and direct sunlight.
2. Unit conversions: °C = (°F - 32) / 1.8 ; °F = (°C × 1.8) + 32.

Prepared by :

侯福麟