




## Technical Data Sheet

# Triethanolamine

2,2',2''-nitrioltriethanol, Ethanol, 2,2',2''-nitrioltris-

CAS Number: **102-71-6**

Formula:  $H(C_2H_4OH)_3$



### DESCRIPTION:

Triethanolamine is a clear, viscous and hygroscopic liquid, with a mild ammonia-like odor.

### APPLICATION:

Triethanolamine (TEA) is used for a chemical intermediate in the manufacture of detergents, personal care products, surfactants, textile specialties, cement additives, cement grinding aids, corrosion inhibitor, dispersant for dyes.

### PHYSICAL PROPERTIES:

Form	Liquid
Appearance	Clear
Molecular Weight	149.2
pH	11
Boiling Point, 760 mm Hg, °C	336
Flash Point, PMCC, °C	179
Melting Point, °C	20.5
Specific gravity, 20/20°C	1.12
Vapor Pressure, mm Hg, 20°C	<0.01

### REGULATORY INFORMATION:

IMDG Classification	Not Regulated
HMIS Code	1-1-0
HS Code	2922.15.00



#### PTT Global Chemical Public Company Limited

Head Office : 555/1, Energy Complex, Building A, 14<sup>th</sup>-18<sup>th</sup> floor, Vibhavadi Rangsit Road, Chatuchak, Chatuchak, Bangkok 10900 Thailand

Tel. : +66 (0) 2265-8400 Fax : +66 (0) 2265-8500

Rayong Plant : 9-9/1 Soi G12, WHA Eastern Industrial Estate (Map Ta Phut), Pakorn Songkhraorat Road, Map Ta Phut, Mueang Rayong, Rayong 21150, Thailand

Tel. : +66 (0) 3899-4000 Fax : +66 (0) 3892-5988

For Enquiry, please contact at EOEG@pttgcgroup.com  
Website : <https://www.pttgcgroup.com/>



### **HANDLING AND STORAGE:**

Keep the material in the anhydrous state to prevent severe corrosion to the carbon steel or aluminum tank and related equipment. For longer term color stability, it is recommended that the product be stored under an inert atmosphere. Ethanolamine products have 24 months of shelf-life time under unopened drum. The product should be re-evaluated after 24 months to reconfirm the product quality, if properly stored and protected from contamination.

For storage conditions, Product is hygroscopic, water contamination should be avoided. Keep container tightly closed without air contamination. The periods of exposure to high temperatures should be minimized. Avoid directly contact with sunlight and higher temperature.

### **PACKAGING:**

Product is available in bulk truck, ISO Tank, IBC tank, steel drum with epoxy phenolic coating. Because of high freezing point of product, steel drum without coating liner (SDNC) is available since it is a particular packaging used for thawing requirement in cold weather country or winter season. Therefore, user should assume product quality concerns of coloration and deterioration. The product in SDNC should be short term storage.

For drum thawing recommendation, the unfreezing should be done by storage in hot room with temperature range of 30-40°C. In another way, the drums are heated by hot water or electric heating coils. But the epoxy-phenolic liner in drums may be degraded by long-term external strap heating, resulting in effect of product quality. Drums must be vented while it is heated to prevent the pressure buildup for safety concern.

### **SAFETY:**

Wear appropriate personal protective equipment, including appropriate respiratory protection. Avoid contact with skin, eyes or clothing. For information on the toxicity and handling of this product, please find in the Material Safety Data Sheet.

### **TERMS & CONDITIONS:**

Copyright © 2022 PTT Global Chemical Public Company Limited. All rights reserved.

All information contained in the document is reliable to the best knowledge of PTT Global Chemical Public Company Limited. The information is intended to describe the product for the purpose of health, safety and environmental requirements only. All users should conduct an adequate study to firm the suitability of any product in regard to such use. In addition, each user should obtain detailed information on toxicity, handling and storage, proper shipping, together with all appropriate health, safety and environmental standards. No representations or warranties, either express or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to information or the product to which that information refers. In no event will PTT Global Chemical Public Company Limited be hereby responsible for loss, damage or expense of any nature whatsoever resulting from the use of or reliance upon the information herein or the product to which that information refers.



#### **PTT Global Chemical Public Company Limited**

**Head Office** : 555/1, Energy Complex, Building A, 14<sup>th</sup>-18<sup>th</sup> floor, Vibhavadi Rangsit Road, Chatuchak, Bangkok 10900 Thailand

Tel. : +66 (0) 2265-8400 Fax : +66 (0) 2265-8500

**Rayong Plant** : 9-9/1 Soi G12, WHA Eastern Industrial Estate (Map Ta Phut), Pakorn Songkhraorat Road, Map Ta Phut, Mueang Rayong, Rayong 21150, Thailand

Tel. : +66 (0) 3899-4000 Fax : +66 (0) 3892-5988

For Enquiry, please contact at [EOEG@pttgcgroup.com](mailto:EOEG@pttgcgroup.com)  
Website : <https://www.pttgcgroup.com/>