



PAN ASIA CHEMICAL CORP
WORLD TRADE BUILDING (11TH FLOOR)
50 SEC.1 ,HSIN SHENG SOUTH RD.,
TAIPEI , TAIWAN 100, ROC
TEL: 886-2-2351-1212 FAX:886-2-2396-2946

Technical Data Sheet

產品名稱 brand name	PANESTER 2619D
化學名稱 chemical name	Neopentylglycol Dioleate
外觀(appearance).....	slight yellowish liquid
WATER content%.....	0.1(max)
色度 COLOR(Gardner).....	2(max)
Saponification Value mg KOH/g.....	175~185
Iodine value mg gl/100g.....	85(max)
Acid value mg KOH/g.....	1(max)
Typical physical properties:	
Viscosity Index	200-210
Viscosity @40°C mm ² /s	22-26
Viscosity @100°C mm ² /s.....	6-7
Flash Point (COC) °C.....	>270
Pour Point °C.....	<-20
包裝 PACKING.....	180kg/iron drum

用途：

適用於調配要求環保的抗燃液壓油、鏈條油等工業用油。

Applications:

PANESTER 2619D can be base oil/additive for environmentally acceptable lubricants, such as HFD-U (fire resistant hydraulic lubricant), and chain oil.