



# 宁波甬华树脂有限公司

## NINGBO YONGHUA RESIN CO.,LTD

Add:No.555 Fengming Road,Ningbo Petrochemical Zone,Ningbo,China.315000

Tel:0086-574-86680024 Fax:0086-574-86680088

[www.nbyhsz.com.cn](http://www.nbyhsz.com.cn) Email:amy@hh-sh.com

## TECHNICAL DATA SHEET

### C5 PETROLEUM RESIN YH-1288S™

#### DESCRIPTION

C5 PETROLEUM RESIN YH-1288S™ is a kind of polymers designed for Hot Melt Road Marking system,the resin show outstanding affinity for pigments and superior processability in the hot melt road marking application.It stable all round the year by adding additive.

#### PERFORMANCE PROPERTIES

Properties	Typical Value	Test Method
Apperance	Yellowish transparent granule	VISUAL TEST
Softening Point( Ring& Ball,C)	98-105	ASTM E28
Color (Ga#)	5Max	ASTM D1544
Bromine Value (Br g/100g)	25 Max	ASTM D1158
Melt viscosity(200C,cps)	≤250	ASTM D 3236
Color Stability(Ga#,200C,3h)	8Max	ASTM D 6605
Ash ( %)	0.05 Max	ASTM 5040

#### PACKING,STORING, TANSPORTING:

Granules in multi-ply HDPE inner bags of 25kgs net weight, 500KG bag also viable. To be stored in cool and dry area and keep away from heat and flame.

*The information given above is based on our experience and laboratory test. It is given without warranty.*

*The customer must make his own trials to ensure that glue meets his requirements.*



NINGBO YONGHUA RESIN Phone:0086-574-86680024 Fax:0086-574-86680088 Web:www.hh-sh.com

A MEMBER OF HENGHE GROUP