



浙江恒河石油化工股份有限公司

**ZHEJIANG HENGHE PETROCHEMICAL CO.,LTD**

Add:No.3511 Yuejintang Road,Ningbo Petrochemical Zone,Ningbo,China.315000

Tel:0086-574-86680024 Fax:0086-574-86680088

[www.hh-sh.com](http://www.hh-sh.com) Email:amy@hh-sh.com

## TECHNICAL DATA SHEET

### C9 PETROLEUM RESIN PR-120™

#### DESCRIPTION

C9 PETROLEUM RESIN PR-120™ is a kind of polymers, it has the properties of good heat stability,intersolubility,viscosity,light stability, it's designed for Paints,rubber,Adhesive,Printing ink industries.

#### PERFORMANCE PROPERTIES

Properties	Typical Value	Test Method
Apperance	Yellowish transparent granule	VISUAL TEST
Softening Point( Ring& Ball,C)	110-120	ASTM E28
Color (Ga#)	10-11	ASTM D1544
Acid Value (KOHmg/g)	0.30 Max	ASTMD 974
Ash (%)	0.05 Max	ASTM 5040

#### PACKING,STORING, TANSPORTING:

Granules in multi-ply HDPE inner bags of 25kgs net weight. To be stored in cool and dry area and keep away from heat and flame.

*The information given above is based on our experience and laboratory test. It is given without warranty.*

*The customer must make his own trials to ensure that glue meets his requirements.*

